

BC Series Modular Fibre Optic Interface System




Description:


- Updated version of the BC100 rack frame with enhanced onboard monitoring and diagnostics
- Holds up to 15 single-slot BC Series fibre optic interface cards
- Dual redundant, hot-swappable front-access PSUs with independent AC inlets and load sharing
- 7" front panel touchscreen displays real-time status of all cards, including signal type, PSU status, voltages, and temperature
- Monitoring and configuration via SNMP v2.1 using optional BM102i or BM103 network card in dedicated Slot 16
- Rear card loading keeps all fibre and copper cabling neatly inside the rack enclosure
- USB port for simple firmware updates from a flash drive
- Available with optional factory-fitted fan card for high-temperature environments (reduces internal temp by ~10°C)
- Ideal for OB/live trucks, fly-away kits, and fixed installations requiring robust, modular fibre transport

BC100i Front Panel display examples

Home Page





Card Info Page



Frame Page



Network Card Page



SFP Info Page(example)

Specifications

BC100i General Specification	
Number of card slots	15 + 1 for network card option
Power supplies	2 x 100W modular units, fully redundant
Power Input	90 to 250 VAC, 47-63 Hz
Fuses	2 x T5AH 250V, integral with AC inlets
Operating temperature range	-30 °C to +70 °C
Dimensions (w x h x d)	445 mm x 132.5 mm (3RU) x 250 mm
Weight	11 kg (fully-loaded)
Warranty	5 years

General Specifications	
EMI/RFI	89/336/EEC, EN55022B, EN61000-4-2, EN61000-4-4 (Level 2), EN61000-4-4FTB, EN61000-4-5, EN61000-4-11
Electrical	EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4
RoHS	Directive 2002/95/EC

Ordering Information

BC100i-3RU	19" 3RU Chassis for up to 15 BCxxx Cards with optional Network Monitoring and Dual Redundant Power Supplies (not supplied). Includes touchscreen display.
BC100i-3RU/48V	19" 3RU Chassis for up to 15 BCxxx Cards with optional Network Monitoring and facility for Dual Redundant Power Supplies (not supplied). Fitted with 48V dc input.
BM102i	Network Monitoring Card with Ethernet connection for Slot-16
BC140	Extender Card for BC100 3RU Chassis
PS100i	90-250VAC Power Supply for BC100i-3RU



Bluebell Opticom Limited,
Unit 2 The Quadrant,
Howarth Rd,
Maidenhead,
Berks,
SL6 1AP, UK
Tel: +44 (0) 1628 510055,
Email: sales@bluebell.tv
Website: www.bluebell.tv

