

Bluebell

Deployable Optical Products for Outside Broadcast



ShaxX-LITE SMPTE Hybrid Alternative Connector Kit for Power Insertion


The ShaxX System from Bluebell has been designed to provide power insertion to broadcast cameras fitted with Standard SMPTE 304M hybrid connectors, thus allowing them to be remotely powered over the hybrid cable. Power can be inserted and transferred to the remote camera which can be up to 300m away. When combined with the Shax-CCU, cameras can be remotely deployed using the ordinary singlemode optical fibre network that may exist within a stadium, campus or metro area.

Shax-LITE is provided in compact footprint for the most cost-effective solutions. It is supplied in a "Multi Camera" version which is switch selectable between major camera manufacturers for easy deployment.

ShaxX-LITE allows the user to replace the fibre/copper hybrid cable between the camera and the CCU with standard fibre cable and relay all the communications and signals. This frees the camera from being tethered to a local mains supply.

The ShaxX-LITE can also be combined with the BC Series Multi-format Interfaces to carry signals from multiple cameras over a single cable. This can help reduce and simplify rigging and installation time. Contact the Sales Office for additional information on the available options.

Front panel LEDs give instant operational feedback of the link status between each camera and CCU. The ShaxX-LITE is enclosed in a robust and ruggedised aluminium enclosure, ideally suited to Outside Broadcast and Fly Away applications. An optional rack mount panel also allows 2 Shax-LITEs to be mounted in standard 19" frames.



Specifications

Optical I/O
 Connector 1 x Lemo FXW.3K.93C.TLC Panel Plug
 Wavelength Independent

Optical I/O
 Connector 2 x female ST, SC, FC
 See Ordering Information
 Wavelength Independent
 Optical Loss < 1 dB per end

Mains Input
 IEC Mains Inlet Selectable rating 115 or 230 V ac.

Conformance
 EMI/RFI Complies with 89/336/EEC
 Electrical Complies with EN 61000-6-1, EN61000-6-2
 RoHS Complies with Directive 2002/95/EC
 IP Rating IP50

General specifications
 Dimensions 320 x 87 x 170mm without handles.
 Operating Temp -20 to +60 °C
 CCU Supply Voltage 36 V dc and 240 V ac
 Weight 3.5 kg
 Warranty 5 years



Ordering Information

ShaxX-LITE-XX SMPTE Hybrid Alternative Connection Kit - Used in conjunction with Shax-CCU allows hybrid fibre enabled cameras to be connected to the CCU over standard fibre networks. Power is inserted into the hybrid cable.

ShaxX-LITE-2U-RACK 19" 2U Mounting Plate for fixing 2 x ShaxX-LITE into a 19" cabinet or flight case. Allows 2 x ShaxX-LITE to be mounted side by side in a 19" cabinet. Support for the rear of the ShaxX-LITE units in the cabinet is recommended.

Key /XX Replace -XX with -ST for ST/PC connectors ST is the standard preferred stock item.
 Replace -XX with -FC for FC/PC connectors
 Replace -XX with -SC for SC/PC connectors

Note: Units are provided in Multi Camera format as the standard factory option. **An individual front panel switch for each channel allows user adjustment for certain Sony, Hitachi and Ikegami cameras.** All Shax and ShaxX units are currently compatible with the following
 Sony HDC-900/950/1000/1500/1700/2500
 Contact the Sales Office for HDC-4300 and F55 camera compatibility
 Hitachi CU-HD1200 camera compatibility
 Ikegami HDK-97GX