


BN Series deployable optical product



Key Features:

- The BN723 provides serial control data over Fibre
- The rugged design allows the unit to be deployed in OB or flypack applications.
- Can be supplied in multimode, singlemode, and CWDM variations to suit all applications, offering a perfect complement to the video to optical converters.
- Power can be supplied direct to the unit from the standard bluebell PS12 or any readily available DC supply found on-site.
- A complimentary modular BC Series card is also available when a 19" rack-based solution is required

BN723 Serial Control data



Specifications

Electrical Input	
Connector	44 Pin D connector
Format	20 Hz-20 kHz± 0.3 dB 2 x RS232 Bi-Directional 2 x RS422/485 Bi-Directional 2 x GPI Bi-Directional
Optical Output	
Connector	1x female LC as standard per channel
Tx wavelength and power plus receive sensitivity are defined by the SFP fitted Typical values are outlined below	TX Power -2dBm@1310nm (typical) - 2dBm@1510nm (typical) 0 dBm@CWDM (typical)
RX Wavelength	1200-1619 nm
RX Sensitivity	> -24dBm@1.25 Gb/s
Max I/P Power	> -1 dBm

General Card Specification	
Depth	92mm
Width	64mm
Height	30mm (Excluding Connectors)
Weight	100g
Operating Temp	-30 to 70°C
Power	2.5 W
Conformance	
EMI/RFI	Complies with 89/336/EEC, EN55022B, EN61000-4-2, EN61000-4-4(level 2), EN61000-4-4FTB, EN61000-4-5, EN61000-4-11
Electrical	Complies with EN61000-6-1, EN61000-6-2, EN61000-6-3, EN61000-6-4
Laser Safety	Dependent on SFP fitted Complies with Class 1 laser product
RoHS	Complies with Directive 2002/95/ec
Warranty	5 Years

Ordering Information

BN723/M	Multimode Data Fibre Optic Transceiver Module. 2 x RS232, 2 x RS422/485 and 2 x GPI over 2 fibres. Fitted with LC connectors. Includes PS12 power supply
BN723/S/13/WB	Singlemode Data Fibre Optic Transceiver Module. 2 x RS232, 2 x RS422/485 and 2 x GPI over 2 fibres. (1310 nm TX and Wideband receiver). Fitted with LC connectors. Includes PS12 power supply.
BN723/S/13/15	Singlemode Data Fibre Optic Transceiver Module. 2 x RS232, 2 x RS422/485 and 2 x GPI over 1 fibre. (1310 nm TX). Used in conjunction with BN723/2/15/13 as a matched pair. Fitted with LC connectors. Includes PS12 power supply.
BN723/S/15/13	Singlemode Data Fibre Optic Transceiver Module. 2 x RS232, 2 x RS422/485 and 2 x GPI over 2 fibres. (1550 nm TX). Used in conjunction with BN723/S/13/15 as a matched pair. Fitted with LC connectors. Includes PS12 power supply.
BN723	Data Fibre Optic Transceiver Base Module. 2 x RS232, 2 x RS422/485 and 2 x GPI over fibre. No Optics Fitted. Includes PS12 Power Supply.
BN723/S/CWDM/xx/WB	Singlemode and Data Fibre Optic Transceiver Module. 2 x Rs232, 2 x RS422/485 and 2 x GPI over 2 fibres. (CWDM TX and Wideband receiver). Fitted with LC connectors. Includes PS12 power supply.



Bluebell Opticom Limited Unit
2 The Quadrant Howarth Rd,
Maidenhead Berks, SL6 1AP
UK Tel: +44 (0) 1628 510055,
Email: sales@bluebell.tv
Website: www.bluebell.tv

