

Bluebell PROBE offers a flexible fibre optic transport solution for field operation.

- Compact and lightweight
- Rugged Case
- Versatile Configuration
- Links to Bluebell Probe or BC100 frame Carries all signal formats including 3G-SDI, HD-SDI, SD-SDI, ASI Composite video AES, analogue audio Data, Ethernet WDM, CWDM
- Battery or mains powered
- Single folding front handle

## General

The Bluebell PROBE is a rugged portable fibre optic system specifically designed for OB, ENG and SNG applications. It has been designed to be used as a "throw-down" box and connected to a truck via a Military Tactical Fibre Optic Cable for the ingest of news, sport and concerts in any outside broadcast environment.

The unit can be configured for almost any combination of Video, Audio and Data and multiples thereof.

A typical setup might be 2 x HD-SDI Program video feeds, Black and Burst Genlock and RS232 Control for connection to a remote camera head.

The unit can be supplied with any type of fibre optic connector to suit the application including SMPTE 311 Hybrid Cables, Neutrik OpticalCON, Hermaphroditic or standard SC, FC connectors.

Applications have been found with many Outside Broadcast vehicles, special event companies and in pre-fibred venues.

Units can also be used in conjunction with standard Bluebell BC100 frames, Blueboxes or BC323 stand alone units.



Probe fitted with optional SMPTE 3K Series Connector



## **General specifications**

Dimensions -BASE3 -BASE6

Temp Range **Humidity Range** Input Voltage Input Voltage

## Conformance

FMI/RFI Electrical Laser Safety

RoHS IP Rating Warranty

270 x 246 x 124 mm (External) 165 x 350 x 180 mm (External) -30 to +70 °C Up to 95% 6 V d.c. @ 1.5A max and/or IFC mains 110/240 V depending upon configuration ordered.

Complies with 89/336/EEC Complies with EN 61000-6-1, EN61000-6-2 Complies with Class 1 laser product 24 CFR 1040.10 & 1040.11 Complies with Directive 2002/95/EC IP67 before configuration on base case

5 years

## Ordering Information

PROBE-BASE6

PROBE-BASE3 A ruggedized portable fibre optic system ideally suited to OB, ENG and SNG applications specifically designed for use

as a "throw down" box. The unit can be configured for any combination of video, audio and data.

Add any combination of up to 3 standard BC Series cards to the base unit. Powered via 4 pin XLR DC input. Power supplied by PS12 external PSU.

A ruggedized portable fibre optic system for any combination of up to 6 standard BC Series cards.

For alternate connectors and options please contact the Sales Office with your requirements.